BEST PACKAGING SYSTEMS INC

Technical Data Sheet

B182 Freezer Grade Supreme Industrial Carton Sealing Tape

PRODUCT
2.00mil Freezer Grade Supreme Industrial Standard Carton Sealing Tape

DESCRIPTION

Film:	Biaxially Oriented Polypropylene
Total Thickness:	2.00 mils
Adhesive:	Emulsion Acrylic
Color:	Clear, Tan, Red, Blue, Green, Orange, Yellow, White, or Black

PHYSICAL PROPERTIES

Tensile Strength (LBS/in):	25 minimum	PSTC-131	(ASTMD3759)
Elongation (% at Break):	160 maximum	PSTC-131	(ASTM D3759)
180° Peel Adhesion (OZ/IN):	22	PSTC-101	(ASTM D3330)
Resistance to UV Light:	Excellent		

APPLICATION TEMPERATURE
32° F to 140° F

OPERATING TEMPERATURE
Has -10°F to 200°F nominal range. Contact your STA representative to determine actual temperature range specific to a particular application.

TYPICAL APPLICATIONS
The industry standard for sealing medium weight cartons subjected to usual shipping hazards in a wide range of temperatures.

GOVERNMENT SPECIFICATIONS
Conforms to FDA Regulations 21 CFR 175.105 and 21 CFR 177.1520

APPLICATION & OPERATING CONDITIONS:
The conditions at which the tape is unwound and applied to the substrate. Under normal conditions, the tape should unwind and adhere to the substrate properly and perform as normally expected. The tape should be used within 1 year of the date of shipment.

NOTES:
The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine their suitability before adapting them on a commercial scale.

For more information, please contact our sales department

8699 Escarpment Way, Unit #1. Milton. ON. L9T 0J5 • Phone: 905 864 3005 • 1 877 484 4440 • Fax: 905 864 6245
www.bestpackagingsystems.com