

Technical Data Sheet

PRODUCT DESCRIPTION

BST180 is an industrial packaging tape used for box sealing, splicing, recoupage and other packaging application. This product has a conformable backing and a consistent pressure sensitive hot melt synthetic rubber adhesive system.

NOMINAL VALUES

The following data are nominal values based on ASTM standard tests. The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Backing (Cast Film)	Biaxially Oriented Polypropylene Film
Adhesive	Synthetic Rubber/Resin
Tensile Strength:	N/A
Machine Direction:	24 lbs/inches width
Cross Direction:	46 lbs/inches width
Elongation at Break:	120 %
Adhesion to Steel:	31.8 oz/inches width
Shear to Linerboard:	900+ minutes
Thickness – Backing:	1.2mil
Total:	1.8mil
Colors:	Clear & Tan

WARRANTY, LIMITED REMEDY AND DISCLAIMER:

Unless an additional warranty is specifically stated on the applicable BEST PACKAGING product packaging or product literature, BEST PACKAGING warrants that each BEST PACKAGING product meets the applicable BEST PACKAGING product specification at the time BEST PACKAGING ships the product.

BEST PACKAGING MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.

If the BEST PACKAGING product does not conform to this warranty, then the sole and exclusive remedy is at BEST PACKAGING's discretion with regards to replacement of the BEST PACKAGING product or refund of the purchase price.

For more information, please contact our sales department

